



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

16CH 2SATA H.265 HD Professional NVR with 8pcs POE ports, Support 1CH Face Detection, VSS Mobile App, ONVIF 2.6, Max 16ch Playback, Max support 16CH 6MP IPC.



Key Features:

Model: NVR-3116-P16/JS

1CH Face Detection or 2CH Circumference analyze, Smart research

Support 16CH Face Detection (Upgrade VSS IPC)

With 8pcs POE ports, H.265 Format, Support ONVIF 2.6 protocol

IP input: 16ch@720/960/1080P / 3.0/4.0MP/5.0MP/6.0MP@30fps

Bandwidth: 128Mbps

Support 2SATA HDD (10TB)

Support Max 1~16ch real-time playback

Audio: 16ch in by RJ45, 1ch in by RCA, 1ch out by RCA

Support Multi-Protocols/P2P/Cloud Storage (google drive/drop box)

Built-in free DDNS/UPNP/3G Dongle supported/Digital zoom/Mobile phone surveillance

1 x VGA port, 1 x RJ45 ports; 1 x HDMI ports; 2 USB2.0 ports, 1 x RS485 port

Remote controlling, Mouse controlling

Mobile phone APP: VSS Mobile (support IOS/Android system)

Computer client controlling (IMS300 platform)

Standard configuration power with POE port ($\leq 200W$)

Offer services:

Offer 2-years product warranties.

Logistics convenient.



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Lower price.

6-8 working day per order.

Applications:

This is the best product of safety field. It and CCTV camera、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community, or a large public places, etc.

Parameters:

Model		NVR3116-P16/JS	NVR3132-P16/JS
OS		Embedded Linux	
Video&Audio input	Bidirectional Talk	1CH, RCA (Line in, 2Vp-p, 1Kohms)	
	Incoming bandwidth	128Mbps	200Mbps
	Outgoing bandwidth	128Mbps	160Mbps
	IPC Input	16CH	32CH
Video&Audio output	VGA	1CH, 1920×1080, 1280×1024, 1280×720, 1024×768	
	HDMI	Standard 1.3a	
		1920×1080, 1280×1024, 1280×720, 1024×768	
	Audio Output	1CH, RCA (Line out, 2Vpp, 300ohms)	
Video&Audio encoding	Audio Compression	G. 711A	
	Audio Bit Rate	64Kbps	
Video&Audio decoding	IP channel Resolution	Main stream: Up to 1920x2048 Auxiliary stream: D1	
	Video decoding	MPEG-4/H. 264(Up to High Profile@Level4.2)	
	Audio decoding	G. 711A/G. 726	
	Synchronous Playback	Up to 16CH	Up to 16CH
	Decoding Ability	13CH 720P@30FPS or 6CH 1080P@30FPS	
Elligent Analysis		1CH Face detection or 2CH Perimeter detection	N/A
		Up to 1080P	
Other Function	Bidirectional Talk	Two-way voice intercom function	
	Motion Detection	Zones: 396(22*18), Sensitivity: 1~6 (level 6 is highest)	
	Picture Capture	Support JPEG Capture	
HDD Interface	SATA	2 SATA Interfaces	
	Max Capacity	Unlimited	
POE Interface	POE Interface	16CH	16CH
		IEEE 802.3af	IEEE 802.3af
		RJ-45 10/100 Mbps self-adaptive Ethernet interface	RJ-45 10/100 Mbps self-adaptive Ethernet interface
	Power	≤200W	≤200W
External Interface	Network Interface	1 RJ45 10M/100M/1000M self-adaptive Ethernet interface	
	USB	2 USB2.0 Interfaces	
Structure	Dimensions	405*365*123mm	
	Front Panel	LED	
	Size	1U, 360*311.5*48mm	
	Weight	3KG (without HDD)	
	Installation	Desktop Installation	



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

General	Power Supply	110V~220V \pm 10%, 47Hz~63Hz	
	Working Temperature	0℃--+55℃	
	Working Humidity	10%--90%	
	Consumption	10W (without HDD, without POE)	10W (without HDD, without POE)