



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

**2.0MP H.265 Waterproof Bullet Starlight IP Camera,
3.0megapixels 3.6mm Starlight HD Fixed Lens, Audio In, POE
Power Supply, VSS Mobile APP.**



Model: RC-BF75P-2SW-P-A

Key features:

3.0-megapixel Starlight 3.6mm HD Fixed Lens (4, 6,8mm optional).
42pieces IR LEDs, 40 meters of IR distance.
White casing with strong bracket.
Normal network video cable.

Product characteristics:

1/2.8" CMOS Sensor (Sony IMX307+Hi3516C V300).
Support H.264/H.265/H.265+ Video compression.
Support Starlight (Day and night all color).
Standard 38*38 single board, Easy to install CCTV Camera.
Support smart IR (Day and night auto switch).



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Max video resolution: 1920*1080@25/30fps.

Support 1ch audio input, 1ch audio output, realize two-way phonetic dialogue.

Support 1ch alarm input.

Support 1 USB reserve interface.

Support 1ch CVBS output.

Support three-bit stream.

Support 3D noise reduction and digital WDR.

Support private network penetration and cross browser access.

Mobile APP name: VSS Mobile.

Support POE power supply.

Product Advantages:

Offer 2-years product warranties.

Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Efficiently working with almost NVR.

Lower price.

6-8 working day per order.

Product applications:

This is the best product of safety field. It and hard disk video recorders、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community, or a large public places, etc.

2MP HD Network Module Parameters:

2MP WD&SL Single-Boards IP Camera Module		
Product model	RC-BF75P-2SW-P-A	
System Structure	DSP	Embedded RTOS, DSP (Hi3516C V300)
	Sensor	1/2.8" CMOS sensor (SONY IMX307)
Video Encoding	Video Encoding	H.265/ H.264High Profile/Main Profile/ Base Line Profile/ MJPEG
		H.265+/ H.264High Profile+/Main Profile+/



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

		Base Line Profile+
	Maximum Image Output	Main stream : 1920*1080@25/30fps; Auxiliary stream 1: 704*576@25/30fps ; Auxiliary stream 2: 1280*720@14/3fps ;
	Streaming transmission	Three stream
	Video Bite rate	32Kbps~8MKbps
Image Enhancement	Min. illumination	Color <u>0.1Lux@F1.2</u> (AGC ON) ; black and white <u>0.01Lux@F1.2</u> (AGC ON)
	Electronic shutter	Auto (1/3 to 1/10000)
	Day/Night switch	color/B&W/Light sensitive switch/Mixed mode switch
	white balance	Auto / Lock white balance / fluorescent lamp /filament lamp /fluorescent lamp /HM
	DNR	2D and 3D DNR
	WDR	Support 120DB Ture WDR
	Video Adjust	Sharpness, Brightness, Saturation, Contrast, Chroma adjustable
	image model	Transparent /real
	color pattern	Standard /gorgeous
	Corridor pattern	support
	backlight compensation	support
	FLC	support
	penetrating fog	support
	image distortion rectifying	support
	Vernier focusing	support (-Z model support)
	All electric rectifier	support (-Z model support)
	Smart IR	support
Interfaces	Signal interface	one photosensitive resistance signal interface, one IR_CUT drive interface support photo resistance signal links to IR-CUT and IR light
	ICR driving voltage	5V
	Smart IR	One port
	Reset interface	One port



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

	Audio interface	One audio in; One audio out
	Alarm interface	One alarm in; One alarm out
	electric zoom interface	One port (-Z model support)
	TTL interface	One port
	CVBS interface	One port
	Power interface	One DC12V power input
	USB interface	One Port
	POE interface	One Extended Interface
	Network light interface	One Port
	Network interface	One RJ45 10/100M Port
Functions	Motion detection	Multiple detection zones, variable sensitivity levels
	Capture function	JPEG , capture resolution is the max coding resolution
	Security	Password protection and water marker
	OSD	Support Channel Name and Time
		Support custom character superposition
		Support image overlay
	storage	Support FTP storage
	Smart function	Tripwire ; Regional invasion ; Items stolen ; Items move ; Density Detection ; Number Stat ; Through the fence ; Wandering detection ; Retrograde motion detection ; Face Capture
	Smart alarm	Network abnormal, cover alarm etc.
	Mobile client	VSSMOBILE for both iPhone and Android system phone
	Protocol support	TCP/IP ; UDP ; HTTP ; IGMP ; ICMP ; DHCP ; RTP/RTSP ; DNS ; DDNS ; FTP ; NTP ; PPPOE ; UPNP ; SMTP ; SNMP
General	Reverse the registered	support
	Interface protocol	ONVIF2.6/CGI/GB28181
	Power Supply	DC12V/POE(-P)
	Power Consumption	<1.5W (without infrared lamp board)
	Lightning Protection	Power, network, POE all lightning protection, meets with standard GB/T17626.5 , and IEC61000-4-5



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

	IR_CUT pitch	20mm
	Size	38*38 (mm) Single Board